



## Spezialprofile warmgewalzt

Bodenbelagswinkelprofile S 235 JR / EN 10025-2




| Profil | Abmessung / mm |    |    |    |   |    |      | kg / m |
|--------|----------------|----|----|----|---|----|------|--------|
| Nr.    | h              | b  | b1 | c  | s | t  |      |        |
| 2442/1 | 40             | 40 | 15 | 5  | 5 | 10 | 3,11 |        |
| 2554   | 50             | 50 | 20 | 5  | 5 | 10 | 4,23 |        |
| 2857   | 50             | 50 | 20 | 7  | 5 | 12 | 4,6  |        |
| 2555   | 50             | 50 | 20 | 7  | 7 | 14 | 5,59 |        |
| 2607   | 50             | 50 | 20 | 10 | 7 | 17 | 5,7  |        |

Handlaufprofile S 235 JR / EN 10025-2



| Profil | Abmessung / mm |    |      |    |     |      | kg / m |
|--------|----------------|----|------|----|-----|------|--------|
| Nr.    | h              | b  | b1   | s  | t   |      |        |
| 680    | 18             | 40 | 19,5 | 8  | 5   | 3,35 |        |
| 681    | 22,5           | 50 | 23   | 10 | 6,5 | 5,3  |        |

Treppenschutzschienen – Profil S 235 JR / EN 10025-2



| Profil             | Abmessung / mm |  |  |  |  |      | kg / m |
|--------------------|----------------|--|--|--|--|------|--------|
| Nr.                | b              |  |  |  |  |      |        |
| entspr. W 62.294.0 | 35             |  |  |  |  | 1,75 |        |