

Spezialprofile

warmgewalzt

T – Profile, breitfüßig, rundkantig, (TB), S 235 JR / EN 10025 – 2
Ungenormte Abmessungen

Profil		Anmessung / mm				kg / m
Nr.	Normbez.	b	h	s	t	
1943		40,0	20,0	4,5	4,5	2,01
352		50,0	25,0	5	5	2,80
2497	TB 30	60,0	30,0	5,5	5,5	3,64
1758	TB 35	70,0	35,0	6	6	4,66
2498	TB 40	80,0	40,0	7	7	6,21
2087 A	TB 50	100,0	50,0	8,5	8,5	9,42
2729	TB 60	120,0	60,0	10	10	13,40

Z – Profile, rundkantig, S 235 JR / EN 10025 – 2
Entsprechend DIN 1027

Profil		Anmessung / mm				kg / m
Nr.	Normbez.	h	b	s	t	
1886	Z 30	30,0	38,0	4,0	4,5	3,36
2384	Z 40	40,0	40,0	4,5	5,0	4,26
2203	Z 50	50,0	43,0	5,0	5,5	5,31
524	Z 60	60,0	45,0	5,0	6,0	6,28
2678	Z 80	80,0	50,0	6,0	7,0	8,64
531	Z 100	100,0	55,0	6,5	8,0	11,30
2727	Z 120	120,0	60,0	7,0	9,0	14,30
2728	Z 140	140,0	65,0	8,0	10,0	18,00
2812	Z 160	160,0	70,0	8,5	11,0	21,60